

DJFB Outdoor Cabinet



Specification :

1. This cabinet has the SS frame , totally four sides symmetry with two double 25mm modulus holes of the assemble plane which can make the inside assemble systems standardly , the accessories can suit to the 14 folds profile materials and more choice for the inside installation
 2. 20mm distance between the double wall panel designed can engender the flue domino effect to make the cabinet has a very strong protection against solar irradiation
 3. The frame has the inimitable water proof design , double panel door with three point lock , Polyurethane Gasket around the door . IP55
 4. The door cover has 25mm salient and 75mm height of rain flashing which has the intact vented holes to make sure the air exchanged
 5. The cabinet can be designed as 19" standard cabinet or customized all by client's requirement
 6. The cabinet can satisfy EMC or Non-EMC base on different equipment
 7. Digital Temperature Unit systems (fans ,heat exchanger or industrial air condition) to ensure the equipment works well in the terrible environment . If there is not much cooling requirement for the cabinet , the cabinet can be assembled with fans or vented by the holes in the lower place of the side panels , there also have the dustproof net attached behind the vented holes
- Surface Treatment :powder coating
 - Material :1.5mm SS frame,others are 2.0mm cold rolled steel
Aluminium , Zinc Magnesium-plated steel and Aluminium panel can be chosen from 2.0mm to 4.0mm thick .
 - Color :
 - Body : RAL 7035
 - Plinth and top cover : SS Frame without painting .
 - Dimension :H1800xW900xD900(mm)
Dimension can be customized!