

Consumer Units



Application

Comby consumer units are designed to suit installations in domestic and commercial installations, easy to install, attractive and highly reliable. Fitted with either sheet steel cover or clear plastic cover for visual inspection of components. Complete with neutral and earth terminals and din rail.

Technical Data

Standard : IEC 439-1 & BS 60439-1
 Max. load : 100 amps
 Max. voltage : 240 Vac, 50/60 Hz
 Range : 7,10,16 and 20 modules
 Degree of protection : IP 30
 Enclosure material : Cold rolled sheet steel
 Box and cover 1 mm
 Enclosure finish : Gray, RAL 7035

Plastic Cover for Surface Mounting



Type No.	Dimensions(mm)	No. of rows	No. of modules	Weight (kg)
	H x W x D			
CUP 107S	256x209x 88	1	7	2.2
CUP 110S	256x263x 88	1	10	2.6
CUP 116S	256x366x 88	1	16	3.2
CUP 120S	256x440x 88	1	20	4.1

Plastic Cover for Flush Mounting

Type No.	Dimensions(mm)	No. of rows	No. of modules	Weight (kg)
	H x W x D			
CUP 107F	276x229x 88	1	7	2.3
CUP 110F	276x283x 88	1	10	2.8
CUP 116F	276x386x 88	1	16	3.5
CUP 120F	276x460x 88	1	20	4.3

Steel Cover for Surface Mounting



Type No.	Dimensions(mm)	No. of rows	No. of modules	Weight (kg)
	H x W x D			
CUS 107S	256x209x 110	1	7	2.8
CUS 110S	256x263x 110	1	10	3.4
CUS 116S	256x366x 110	1	16	4.4
CUS 120S	256x440x 110	1	20	4.8

Steel Cover for Flush Mounting

Type No.	Dimensions(mm)	No. of rows	No. of modules	Weight (kg)
	H x W x D			
CUS 107F	276x229x 110	1	7	2.9
CUS 110F	276x283x 110	1	10	3.6
CUS 116F	276x386x 110	1	16	4.7
CUS 120F	276x460x 110	1	20	5.0

Application

Housemaster consumer units are designed to suit installations in residential commercial and industrial installations, easy to install and highly reliable. Fitted with sheet steel cover for visual inspection of components. Complete with neutral and earth terminals. Unit comes complete with incoming devices. Surface mounting only, (flush on request).

Technical Data

Standard : IEC 439-1 & BS 60439-1
 Max. load : 100 amps
 80 amps for 4 way RCCB
 Max. voltage : 240 Vac, 50/60 Hz
 Range : 4,7,11,16 and 20 SP & N ways
 Split load, 8, 12, 16 ways
 Degree of protection : IP 30
 Enclosure material : Cold rolled sheet steel
 Box and cover 1 mm
 Enclosure finish : Gray, RAL 7035

Housemaster Sheet Steel Range Isolator (100A) Incomer



Type No.	Dimensions(mm)	No. of ways	Weight (kg)
	H x W x D		
CUMS 04C	256x115x 110	4	2.4
CUMS 07C	256x210x 110	7	3.1
CUMS 11C	256x282x 110	11	3.7
CUMS 16C	256x368x 110	16	4.7
CUMS 20C	256x440x 110	20	5.1

RCCB (F202AC/100/0.03A) Incomer, for HSRC 04C (F202AC/80C0.03A)

Type No.	Dimensions(mm)	No. of ways	Max. load A	Weight (kg)
	H x W x D			
CURC 04C	256x115x 110	4	80	2.5
CURC 07C	256x210x 110	7	100	3.2
CURC 11C	256x282x 110	11	100	3.8
CURC 16C	256x368x 110	16	100	4.8
CURC 20C	256x440x 110	20	100	5.2

Split Load (E202/100A+F202AC/80/0.03A) Incomer

Type No.	Dimensions(mm)	No. of ways	Weight (kg)
	H x W x D		
CUSL 4+4C	256x282x 110	4+4	4.1
CUSL 6+6C	256x368x 110	6+6	5.1
CUSL 8+8C	256x440x 110	8+8	5.5