

Enclosure and door with lock system,galvanised mounting plate,
gland plate,sealing gasket and fixing accessories.

Mounting plate:1.2mm,1.5mm,2.0mm,galvanized steel

SA® UL CE V RoHS CCC

Technical drawing of a rectangular frame. The drawing includes two views: a front view (top) and a side view (bottom). The front view shows a rectangle with a width of $l_{max}15$ and a height of 90 . The side view shows a rectangle with a width of 25 and a height of 2.5 . The drawing also includes labels for dimensions: $l_{max}15$, 90 , 25 , 2.5 , 30 , 45 , 40 , 10 , 15 , 20 , 25 , 30 , 35 , 40 , 45 , 50 , 55 , 60 , 65 , 70 , 75 , 80 , 85 , 90 , 95 , 100 , 105 , 110 , 115 , 120 , 125 , 130 , 135 , 140 , 145 , 150 , 155 , 160 , 165 , 170 , 175 , 180 , 185 , 190 , 195 , 200 , 205 , 210 , 215 , 220 , 225 , 230 , 235 , 240 , 245 , 250 , 255 , 260 , 265 , 270 , 275 , 280 , 285 , 290 , 295 , 300 , 305 , 310 , 315 , 320 , 325 , 330 , 335 , 340 , 345 , 350 , 355 , 360 , 365 , 370 , 375 , 380 , 385 , 390 , 395 , 400 , 405 , 410 , 415 , 420 , 425 , 430 , 435 , 440 , 445 , 450 , 455 , 460 , 465 , 470 , 475 , 480 , 485 , 490 , 495 , 500 , 505 , 510 , 515 , 520 , 525 , 530 , 535 , 540 , 545 , 550 , 555 , 560 , 565 , 570 , 575 , 580 , 585 , 590 , 595 , 600 , 605 , 610 , 615 , 620 , 625 , 630 , 635 , 640 , 645 , 650 , 655 , 660 , 665 , 670 , 675 , 680 , 685 , 690 , 695 , 700 , 705 , 710 , 715 , 720 , 725 , 730 , 735 , 740 , 745 , 750 , 755 , 760 , 765 , 770 , 775 , 780 , 785 , 790 , 795 , 800 , 805 , 810 , 815 , 820 , 825 , 830 , 835 , 840 , 845 , 850 , 855 , 860 , 865 , 870 , 875 , 880 , 885 , 890 , 895 , 900 , 905 , 910 , 915 , 920 , 925 , 930 , 935 , 940 , 945 , 950 , 955 , 960 , 965 , 970 , 975 , 980 , 985 , 990 , 995 , 1000 .

Model	Dimensions (mm)			No. of lock
	W	H	D	
DJ-ECDR8 620	800	600	200	1
DJ-ECDR8 625	800	600	250	1
DJ-ECDR8 630	800	600	300	1
DJ-ECDR8 640	800	600	400	1
DJ-ECDR10 620	1000	600	200	1
DJ-ECDR10 625	1000	600	250	1
DJ-ECDR10 630	1000	600	300	1
DJ-ECDR10 640	1000	600	400	1
DJ-ECDR12 620	1200	600	200	1
DJ-ECDR12 625	1200	600	250	1
DJ-ECDR12 630	1200	600	300	1
DJ-ECDR12 640	1200	600	400	1
DJ-ECDR8 820	800	800	200	1
DJ-ECDR8 825	800	800	250	1
DJ-ECDR8 830	800	800	300	1
DJ-ECDR8 840	800	800	400	1
DJ-ECDR10 820	1000	800	200	1
DJ-ECDR10 825	1000	800	250	1
DJ-ECDR10 830	1000	800	300	1
DJ-ECDR10 840	1000	800	400	1
DJ-ECDR12 820	1200	800	200	1
DJ-ECDR12 825	1200	800	250	1
DJ-ECDR12 830	1200	800	300	1
DJ-ECDR12 840	1200	800	400	1
DJ-ECDR10 1020	1000	1000	200	1
DJ-ECDR10 1025	1000	1000	250	1
DJ-ECDR10 1030	1000	1000	300	1
DJ-ECDR10 1040	1000	1000	400	1
DJ-ECDR12 1020	1200	1000	200	1
DJ-ECDR12 1025	1200	1000	250	1
DJ-ECDR12 1030	1200	1000	300	1
DJ-ECDR12 1040	1200	1000	400	1
DJ-ECDR10 1220	1000	1200	200	1
DJ-ECDR10 1225	1000	1200	250	1
DJ-ECDR10 1230	1000	1200	300	1
DJ-ECDR10 1240	1000	1200	400	1

www.daginelectrical.com